

Unit model		MT06R.NR0	MT08R.NR0	CT09F.NR0	CT12F.NR0	CT18F.NQ0	CT24F.NB0
Productgroep		241	241	241	241	241	241
Artikelnummer binnenunit		459.291	459.292	459.611	459.612	459.613	459.614
Chassis code		TR	TR	TR	TR	TQ	TP
Koelcapaciteit Nom. *	kW *	1,5	2,1	2,5	3,4	5,0	6,7
Verwarmingscapaciteit Nom. **	kW **	1,7	2,3	3,2	4,1	5,7	7,5
Luchtdebiet Laag/Midden/Hoog	M³/h	300/360/450	300/360/450	360/420/510	420/480/570	660/720/780	780/900/1020
Ontvochtiging	ltrs/h	-	-	0,9	1,4	2,0	2,7
Geluidsniveau *** Laag/Midden/Hoog	dB(A)	24/27/31	24/27/31	30/33/36	32/35/38	36/39/41	34/36/38
Geluidsvermogen	dB(A)	48	48	52	52	57	57
Afmetingen BxHxD	mm	570x214x570	570x214x570	570x214x570	570x214x570	570x256x570	840x204x840
Gewicht	kg	11,7	11,7	13,0	13,0	14,3	20,5

Rooster model		PT-QCHW0	PT-QCHW0	PT-QCHW0	PT-QCHW0	PT-QCHW0	PT-MCHW0
Artikelnummer rooster		457.933	457.933	457.933	457.933	457.933	457.932
Afmetingen (BxDxH)	mm	620x620x34	620x620x34	620x620x34	620x620x34	620x620x34	950x950x34
Gewicht	kg	2,85	2,85	2,85	2,85	2,85	2,85

Elektrische gegevens

Voeding	Ø/V/Hz	1/230/50	1/230/50	1/230/50	1/230/50	1/230/50	1/230/50
Opgenomen vermogen koelen	kW	0,020	0,020	0,022	0,026	0,026	0,050
Opgenomen vermogen verwarmen	kW	0,020	0,020	0,022	0,026	0,026	0,050
Nom. stroomsterkte koelen / verwarmen	A	0,40	0,40	0,40	0,40	0,40	0,60
Voedingskabel vanaf		Buitenunit	Buitenunit	Buitenunit	Buitenunit	Buitenunit	Buitenunit
Bekabeling tussen binnen / buitenunit	Q x mm²	4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5

Koeltechnisch

Vloeistofleiding	mm(inch)	6,35(1/4)	6,35(1/4)	6,35(1/4)	6,35(1/4)	6,35(1/4)	6,35(1/4)
Gasleiding	mm(inch)	9,52(3/8)	9,52(3/8)	9,52(3/8)	9,52(3/8)	12,7(1/2)	12,7(1/2)
Bijvulling per meter	gram	20	20	20	20	20	20
PED		art. 3 lid 3	art. 3 lid 3	art. 3 lid 3	art. 3 lid 3	art. 3 lid 3	art. 3 lid 3

Algemeen

Condensafvoer aansluitdiameter od/id	mm	Ø 32/25	Ø 32/25	Ø 32/25	Ø 32/25	Ø 32/25	Ø 32/25
Condenswaterpomp aanwezig		Ja	Ja	Ja	Ja	Ja	Ja