

| Binnenunit                          | CT12F.NRO      | CT18F.NQO       | CT24F.NBO      | UT30F.NBO       | UT36F.NAO       | UT42F.NAO         |
|-------------------------------------|----------------|-----------------|----------------|-----------------|-----------------|-------------------|
| <b>Productgroep</b>                 | 249            | 249             | 249            | 249             | 249             | 249               |
| <b>Artikelnummer binnenunit</b>     | <b>459.612</b> | <b>459.613</b>  | <b>459.614</b> | <b>459.615</b>  | <b>459.616</b>  | <b>459.617</b>    |
| <b>Artikelnummer rooster</b>        | <b>459.691</b> | <b>459.691</b>  | <b>459.692</b> | <b>459.692</b>  | <b>459.692</b>  | <b>459.692</b>    |
| <b>Chassis code</b>                 | TR             | TQ              | TP             | TP              | TM              | TM                |
| Koelcapaciteit Nominaal             | kW             | 3,50            | 5,30           | 7,00            | 8,00            | 10,00             |
| Verwarmingscapaciteit Nominaal      | kW             | 3,90            | 5,70           | 7,70            | 9,00            | 11,00             |
| Luchtdebit Laag/Midden/Hoog         | M³/h           | 420/480/570     | 660/720/780    | 780/900/1.020   | 900/1.020/1.140 | 1.200/1.500/1.800 |
| Koelleiding diameter vloeistof Cac  | mm(inch)       | 6,35(1/4)       | 6,35(1/4)      | 9,52(3/8)       | 9,52(3/8)       | 9,52(3/8)         |
| Koelleiding diameter gasleiding Cac | mm(inch)       | 9,52(3/8)       | 12,7(1/2)      | 15,88(5/8)      | 15,88(5/8)      | 15,88(5/8)        |
| Condensafvoer aansluitdiameter      | mm             | Ø 32            | Ø 32           | Ø 32            | Ø 32            | Ø 32              |
| Ontvochtiging                       | ltrs/h         | 1,70            | 2,10           | 2,40            | 2,50            | 2,70              |
| Geluidsdrukniveau Laag/Midden/Hoog  | dB             | 32/35/38        | 36/39/41       | 34/36/38        | 35/37/40        | 40/43/46          |
| Geluidsvermogen                     | dB             | 52              | 57             | 57              | 58              | 62                |
| Afmetingen (BxDxH)                  | mm             | 570x570x214     | 570x570x256    | 840x840x204     | 840x840x204     | 840x840x288       |
| Gewicht                             | kg             | 14,0            | 14,3           | 20,5            | 20,5            | 24,6              |
| <b>Rooster model</b>                |                | <b>PT-QAGW0</b> |                | <b>PT-AAGW0</b> |                 |                   |
| <b>Afmetingen (BxDxH)</b>           | mm             | 620x620x34      |                |                 | 950x950x35      |                   |
| <b>Gewicht</b>                      | kg             | 3,4             |                |                 | 6,3             |                   |
| <b>PED</b>                          |                | art. 4 lid 3    |                |                 | art. 4 lid 3    |                   |