

Binnenunit model		UM12FH.N10	UM18FH.N10	UM24FH.N20	UM30FH.N20
Productgroep		241	241	241	249
Artikelnummer binnenunit		459.672	459.673	459.674	459.675
Chassis code		M1	M1	M2	M2
Koelcapaciteit Min. / Nom. ⁽¹⁾ / Max.	kW	1,6/3,5/5,1	2,0/5,0/6,0	2,7/6,8/8,3	3,1/7,8/9,3
Verwarmingscapaciteit Min. / Nom. ⁽²⁾ / Max.	kW	1,6/4,0/5,8	2,3/5,8/7,0	3,0/7,5/9,4	3,6/9,0/10,7
Verwarmingscapaciteit bij -10°C	kW	3,53	5,22	7,11	7,88
Luchtdebiet koelen Laag/Midden/Hoog	M³/h	780/870/990	840/960/1.050	1.260/1.440/1.680	1.260/1.440/1.680
Luchtdebiet verwarmen Laag/Midden/Hoog	M³/h	780/870/990	840/960/1.050	1.260/1.440/1.680	1.260/1.440/1.680
Externe statische druk Min./Max.	Pa	20-147	20-147	20-147	20-147
Ontvochtiging	ltrs/h	0,4	1,3	1,2	2,2
Geluidsdrukniveau ⁽³⁾ Laag/Midden/Hoog	dB(A)	30/32/34	32/34/35	34/35/37	33/34/36
Geluidsvermogen Max.	dB(A)	56	60	59	59
Afmetingen (BxDxH)	mm	900x700x270	900x700x270	1.250x700x270	1.250x700x270
Gewicht	kg	24,8	25,8	37,3	37,3