

Binnenunit	CT09F NRO	CT12F NRO	CT18F NQ0	CT24F NBO	UT30F NBO
Productgroep	241	241	241	241	249
Artikelnummer binnenunit	459.611	459.612	459.613	459.614	459.615
Prijs binnenunit	€				

COMBINATIE

		CT09F NRO	CT12F NRO	CT18F NQ0	CT24F NBO	UT30F NBO
Chassis code		TR	TR	TQ	TP	TP
Koelcapaciteit Min. / Nom. ⁽¹⁾ / Max.	kW	1,5 / 2,5 / 3,2	1,5 / 3,4 / 4,5	2,0 / 5,0 / 5,8	2,7 / 6,8 / 8,0	3,2 / 8,0 / 9,2
Verwarmingscapaciteit Min. / Nom. ⁽²⁾ / Max.	kW	1,8 / 3,2 / 3,7	1,8 / 4,1 / 5,0	2,3 / 5,7 / 6,6	3,0 / 7,5 / 9,0	3,6 / 8,9 / 10,1
Verwarmingscapaciteit bij -7°C°C / -10°C	kW	2,7/3,3	4,4/4,9	8,0/7,8	8,6/8,7	10,9/11,6
Luchtdebiet koelen Laag/Midden/Hoog	M³/h	360/420/510	420/480/570	660/720/780	840/930/1.080	930/1.020/1.140
Luchtdebiet verwarmen Laag/Midden/Hoog	M³/h	360/420/510	420/480/570	660/720/780	840/930/1.080	930/1.020/1.140
Ontvochtiging	ltrs/h	0,63	1,26	1,89	2,8	2,8
Geluidsdruk niveau ⁽³⁾ Laag/Midden/Hoog	dB(A)	30/33/36	32/35/38	37/39/41	34/36/38	35/37/40
Geluidsvermogen Max.	dB	52	52	57	53	57
Afmetingen (BxDxH)	mm	570x570x214	570x570x214	570x570x256	840x840x204	840x840x204
Gewicht	kg	12,4	12,4	13,9	21,1	21,1

Energie gegevens						
SCOP		4,30	3,71	3,74	3,83	3,40
Jaarlijks energieverbruik koelen / verwarmen ⁽⁴⁾	KWh	131/980	178/980	273/1.335	322/1.823	394/1.823
Energielabel koelen / verwarmen		A++ / A+	A++ / A+	A++ / A+	A++ / A+	A++ / A+

Koeltechnisch						
Koelleiding diameter vloeistof	mm(inch)	6,35(1/4)		6,35(1/4)		9,52(3/8)
Koelleiding diameter gasleiding	mm(inch)	9,52(3/8)		12,7 (1/2)		15,88 (5/8)
Min./Max. leidinglengte	Mtr.	5,0 / 20,0		5,0 / 30,0		5,0 / 50,0
Max. hoogteverschil binnen / buitenunit	Mtr.	15		30		30
Nominale koudemiddelvulling	kg	0,90		1,10		1,60
Standaard voorgevuld tot	Mtr.	7,5		7,5		7,5
Bijvulling per meter	gram	20		20		40
GWP		675		675		675
T-CO ₂ Equivalent		0,675		0,81		1,283

Algemeen						
Condensafvoer aansluitdiameter Bi/Bu	mm Ø	25/32	25/32	25/32	25/32	25/32
Condenspomp aanwezig		Ja	Ja	Ja	Ja	Ja

Rooster model		PT-QAGW0	PT-QAGW0	PT-QAGW0	PT-AAGW0	PT-AAGW0
Artikelnummer rooster		459.691	459.691	459.691	459.692	459.692
Prijs rooster	€					
Afmetingen (BxDxH)	mm	620x620x34	620x620x34	620x620x34	950x950x35	950x950x35
Gewicht	kg	3,0	3,0	3,0	7,1	7,1

Bediening		PREMTB001	PREMTB001	PREMTB001	PREMTB001	PREMTB001
Artikelnummer		456.139	456.139	456.139	456.139	456.139
Prijs						

Buitenunit		UUA1 ULO	UUA1 ULO	UUB1 U20	UUC1 U40	UUC1 U40
Artikelnummer		459.601	459.601	459.602	459.603	459.603
Prijs	€					